




© 2012, Casella USA, All rights reserved.





CEL-63x Octave and Interval Meter

- Full single measurement range from 20 to 140 dB, Type 1 or Type 2
- Brilliant backlit color graphic display
- Overall results, interval periods and time history profiles saved
- Data marking, back erase and audio recording of events
- USB connection to PC or mini-printer for easy download or field citation
- Real time octave and third octave band models for frequency analysis
 Casella products
 Data compatibility to prior
- Long term environmental measurement kits with accessories

Insight Software - for all Casella & CEL devices

- Provides managerial level analysis of exposure by cohort group, task, process, department, site, etc.
- Easy to use, flexible graphing features
- Simple common interface: fast set-up and download of all Casella products
- Data compatibility to prio Casella s/w
- Store all downloaded data securely with backup and restore facility
- Export to popular office programs


CEL-960 Human Vibration Analyzer

- Hand-Arm and Whole-Body Measurement
- Complete System with sensors and adapters
- Weighted Filters per ISO & ANSI standards
- 1/3 Octave Frequency Data
- Records & Stores Vibration Waveform
- Wide Dynamic range with no adjustment
- Compact, lightweight design
- Bluetooth remote / real time PC display
- One-button operation

Rechargeable Battery

CEL-24x series Sound Level Meter

- Simple, Durable and Accurate NIST traceable calibration
- Measurement range: 30 to 130 dB
- A and C weighted frequency scales
- Slow, Fast and Impulse response
- Measures instant, maximum and average levels
- Time history display with optional data logging
- USB output to PC for data download
- Meets ANSI and IEC Type 2 standards



CEL-35x series Noise Dosimeter

- Built-in microphone: Cable-free design
- Acquires all exposure level data simultaneously: OSHA HCP/PEL, ACGIH
 - <u>any</u> combo: Ex rate, Threshold, Criterion
- Intrinsically Safe versions available
- LCD display of dose and TWA values
- LED status indicator (user selectable)
- 1 minute time history data logging
- Rechargeable battery fast re-charge
- Available individually or in kits of up to 12 dosimeters with accessories

CEL-62x series Octave Band Meter

- Single range from 20 to 140 dB
- Brilliant full color graphic display
- Capture all noise variables simultaneously (A,C,Z weighting, Fast, Slow, Impulse detector)
- Overall results saved in memory
- USB connection: text, csv file formats
- Real time octave and third octave band models for frequency analysis
- Measurement kits with software





More Great Products from Casella:

Tuff™ Personal Air Sampling Pumps MicrodustPro™ Real-time Particulate Monitor Digital Light Meters Digital Anemometers

Casella CEL Inc.

415 Lawrence Bell Dr. Unit 4 / Buffalo, NY 14221 Phone: 800-366-2966 / Fax: 716-276-3043 info@casellausa.com / www.casellausa.com

A Subsidiary of IDEAL INDUSTRIES, INC.

